



L050 제이콥 폴리(벨트폭 12.7mm용 폴리)


호칭	폴리 타입	부쉬 번호	최대 허용 축경	R ∅	S ∅	U ∅	e ∅	W	H ∅	Y	Z	플랜지	소재
JC 18 L 050	1	1108	28	54,57	53,81	—	62	19	47	22	3	플랜지 타입	cast iron
JC 19 L 050	1	1108	28	57,61	56,84	—	62	19	47	22	3		
JC 20 L 050	1	1108	28	60,64	59,88	—	67	19	48	22	3		
JC 21 L 050	1	1108	28	63,67	62,91	—	67	19	48	22	3		
JC 22 L 050	1	1108	28	68,70	65,94	—	73	19	51	22	3		
JC 23 L 050	1	1108	28	69,73	68,97	—	73	19	51	22	3		
JC 24 L 050	1	1108	28	72,77	72,01	—	80	19	58	22	3		
JC 25 L 050	1	1108	28	75,80	75,04	—	80	19	58	22	3		
JC 26 L 050	1	1108	28	78,83	78,07	—	88	19	58	22	3		
JC 27 L 050	1	1108	28	81,86	81,10	—	88	19	58	22	3		
JC 28 L 050	1	1108	28	84,89	84,13	—	94	19	58	22	3		
JC 29 L 050	1	1108	28	87,93	87,16	—	94	19	58	22	3		
JC 30 L 050	1	1108	28	90,96	90,20	—	98	19	58	22	3		
JC 32 L 050	1	1108	28	97,02	96,26	—	100	19	58	22	3		
JC 33 L 050	1	1108	28	100,05	99,29	—	108	19	58	22	3		
JC 34 L 050	1	1108	28	103,08	103,32	—	108	19	58	22	3		
JC 35 L 050	6	1108	28	106,12	105,35	84	113	19	58	22	3		
JC 36 L 050	6	1108	28	109,15	108,39	84	113	19	58	22	3		
JC 40 L 050	1	1610	42	121,28	120,52	—	129	19	90	25	6		
JC 41 L 050	1	1610	42	124,31	123,55	—	129	19	90	25	6		
JC 42 L 050	6	1610	42	127,34	126,58	110	137	19	90	25	6		
JC 44 L 050	6	1610	42	133,40	132,64	110	142	19	90	25	6		
JC 45 L 050	6	1610	42	136,44	135,67	118	142	19	90	25	6		
JC 47 L 050	6	1610	42	142,50	141,74	126	149	19	90	25	6		
JC 48 L 050	6	1610	42	145,53	144,77	126	151	19	90	25	6		
JC 49 L 050	9	1610	42	148,56	147,80	132	—	19	90	25	6		
JC 50 L 050	9	1610	42	151,60	150,83	132	—	19	90	25	6		
JC 52 L 050	9	1610	42	157,66	156,90	138	—	19	90	25	6		
JC 56 L 050	9	1610	42	169,79	169,02	152	—	19	90	25	6		
JC 57 L 050	9	1610	42	172,82	172,06	152	—	19	90	25	6		
JC 60 L 050	16	1610	42	181,91	181,15	162	—	19	90	25	3		
JC 65 L 050	13	1610	42	197,07	196,31	178	—	19	90	25	3		
JC 66 L 050	13	1610	42	200,11	199,34	178	—	19	90	25	3		
JC 72 L 050	13	1610	42	218,30	217,54	199	—	19	90	25	3		
JC 84 L 050	13	1610	42	254,68	253,92	235	—	19	90	25	3		
JC 90 L 050	13	1610	42	272,87	272,11	253	—	19	90	25	3		
JC 96 L 050	13	2012	50	291,06	290,30	270	—	19	110	32	6,5		
JC 120 L 050	13	2012	50	363,83	363,07	344	—	19	110	32	6,5		




1




2




3




4




5



6



7




8


9

L075 제이콥 폴리(벨트폭 19mm용 폴리)


호칭	폴리 타입	부쉬 번호	최대 허용 축경	R ∅	S ∅	U ∅	e ∅	W	H ∅	Y	Z	플랜지	소재
JC 18 L 075	4	1108	28	54,57	53,81	38	62	25	—	22	3	플랜지 타입	cast iron
JC 19 L 075	4	1108	28	57,61	56,84	38	62	25	—	22	3		
JC 20 L 075	4	1108	28	60,64	59,88	46	67	25	—	22	3		
JC 21 L 075	4	1108	28	63,67	62,91	46	67	25	—	22	3		
JC 22 L 075	4	1108	28	68,70	65,94	46	73	25	—	22	3		
JC 23 L 075	4	1108	28	69,73	68,97	46	73	25	—	22	3		
JC 24 L 075	4	1108	28	72,77	72,01	53	80	25	—	22	3		
JC 25 L 075	4	1108	28	75,80	75,04	53	80	25	—	22	3		
JC 26 L 075	4	1108	28	78,83	78,07	60	88	25	—	22	3		
JC 27 L 075	4	1108	28	81,86	81,10	60	88	25	—	22	3		
JC 28 L 075	4	1108	28	84,89	84,13	65	94	25	—	22	3		
JC 29 L 075	4	1108	28	87,93	87,16	65	94	25	—	22	3		
JC 30 L 075	4	1108	28	90,96	90,20	68	98	25	—	22	3		
JC 32 L 075	4	1108	28	97,02	96,26	76	100	25	—	22	3		
JC 33 L 075	4	1108	28	100,05	99,29	83	108	25	—	22	3		
JC 34 L 075	4	1108	28	103,08	103,32	85	108	25	—	22	3		
JC 35 L 075	2	1610	42	106,12	105,35	—	113	25	—	25	—		
JC 36 L 075	2	1610	42	109,15	108,39	—	113	25	—	25	—		
JC 40 L 075	2	1610	42	121,28	120,52	—	129	25	—	25	—		
JC 41 L 075	2	1610	42	124,31	123,55	—	129	25	—	25	—		
JC 42 L 075	7	1610	42	127,34	126,58	110	137	25	90	25	—		
JC 44 L 075	7	1610	42	133,40	132,64	110	142	25	90	25	—		
JC 45 L 075	7	1610	42	136,44	135,67	118	142	25	90	25	—		
JC 47 L 075	7	1610	42	142,50	141,74	126	149	25	90	25	—		
JC 48 L 075	7	1610	42	145,53	144,77	126	151	25	90	25	—		
JC 49 L 075	10	1610	42	148,56	147,80	132	—	25	90	25	—		
JC 50 L 075	10	1610	42	151,60	150,83	132	—	25	90	25	—		
JC 52 L 075	10	1610	42	157,66	156,90	138	—	25	90	25	—		
JC 56 L 075	10	1610	42	169,79	169,02	152	—	25	90	25	—		
JC 57 L 075	10	1610	42	172,82	172,06	152	—	25	90	25	—		
JC 60 L 075	10	1610	42	181,91	181,15	162	—	25	90	25	—		
JC 65 L 075	10	1610	42	197,07	196,31	178	—	25	90	25	—		
JC 66 L 075	10	1610	42	200,11	199,34	178	—	25	90	25	—		
JC 72 L 075	14	1610	42	218,30	217,54	199	—	25	90	25	—		
JC 84 L 075	13	2012	50	254,68	253,92	235	—	25	110	32	3,5		
JC 90 L 075	13	2012	50	272,87	272,11	253	—	25	110	32	3,5		
JC 96 L 075	13	2012	50	291,06	290,30	270	—	25	110	32	3,5		
JC 120 L 075	13	2012	50	363,83	363,07	344	—	25	110	32	3,5		




10



11



12



13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34


35

36


37

L100 제이콥폴리(벨트폭 25.4^m/m용 폴리)


호칭	폴리 타입	부쉬 번호	최대 허용 축경	R ∅	S ∅	U ∅	e ∅	W	H ∅	Y	Z	플랜지	소재
JC 18 L 100	4	1108	28	54,57	53,81	38	62	32	—	22	10	플랜지 타입	cast iron
JC 19 L 100	4	1108	28	57,61	56,84	38	62	32	—	22	10		
JC 20 L 100	4	1108	28	60,64	59,88	46	67	32	—	22	10		
JC 21 L 100	4	1108	28	63,67	62,91	46	67	32	—	22	10		
JC 22 L 100	4	1108	28	68,70	65,94	46	73	32	—	22	10		
JC 23 L 100	4	1108	28	69,73	68,97	46	73	32	—	22	10		
JC 24 L 100	4	1108	28	72,77	72,01	53	80	32	—	22	10		
JC 25 L 100	4	1108	28	75,80	75,04	53	80	32	—	22	10		
JC 26 L 100	4	1108	28	78,83	78,07	60	88	32	—	22	10		
JC 27 L 100	4	1108	28	81,86	81,10	60	88	32	—	22	10		
JC 28 L 100	4	1108	28	84,89	84,13	65	94	32	—	22	10		
JC 29 L 100	4	1210	32	87,93	87,16	68	94	32	—	25	7		
JC 30 L 100	4	1210	32	90,96	90,20	68	98	32	—	25	7		
JC 32 L 100	4	1210	32	97,02	96,26	76	100	32	—	25	7		
JC 33 L 100	4	1610	42	100,05	99,29	83	108	32	—	25	7		
JC 34 L 100	4	1610	42	103,08	103,32	85	108	32	—	25	7		
JC 35 L 100	4	1610	42	106,12	105,35	85	113	32	—	25	7		
JC 36 L 100	4	1610	42	109,15	108,39	85	113	32	—	25	7		
JC 40 L 100	4	1610	42	121,28	120,52	100	129	32	—	25	7		
JC 41 L 100	4	1610	42	124,31	123,55	100	129	32	—	25	7		
JC 42 L 100	8	1610	42	127,34	126,58	110	137	32	90	25	7		
JC 44 L 100	8	1610	42	133,40	132,64	110	142	32	90	25	7		
JC 45 L 100	8	1610	42	136,44	135,67	118	142	32	90	25	7		
JC 47 L 100	8	1610	42	142,50	141,74	126	149	32	90	25	7		
JC 48 L 100	8	1610	42	145,53	144,77	126	151	32	90	25	7		
JC 49 L 100	11	1610	42	148,56	147,80	132	—	32	90	25	7		
JC 50 L 100	11	1610	42	151,60	150,83	132	—	32	90	25	7		
JC 52 L 100	11	1610	42	157,66	156,90	138	—	32	90	25	7		
JC 56 L 100	11	1610	42	169,79	169,02	152	—	32	90	25	7		
JC 57 L 100	11	1610	42	172,82	172,06	152	—	32	90	25	7		
JC 60 L 100	12	1610	42	181,91	181,15	162	—	32	90	25	3,5		
JC 65 L 100	12	1610	42	197,07	196,31	178	—	32	90	25	3,5		
JC 66 L 100	12	1610	42	200,11	199,34	178	—	32	90	25	3,5		
JC 72 L 100	14	2012	50	218,30	217,54	235	—	32	110	32	—		
JC 84 L 100	14	2012	50	254,68	253,92	199	—	32	110	32	—		
JC 90 L 100	14	2012	50	272,87	272,11	253	—	32	110	32	—		
JC 96 L 100	14	2012	50	291,06	290,30	270	—	32	110	32	—		
JC 120 L 100	14	2012	50	363,83	363,07	344	—	32	110	32	—		




10




11




12




13



14



15



16


H100 제이콥 폴리(벨트폭 25.4^m/m 용 폴리)

호칭	폴리 타입	부쉬 번호	최대 허용 축경	R ∅	S ∅	U ∅	e ∅	W	H ∅	Y	Z	플랜지	소재
JC 14 H 100	4	1108	28	56,60	55,23	37	62	31	—	22	9	플랜지 타입	cast iron
JC 15 H 100	4	1108	28	60,64	59,27	37	67	31	—	22	9		
JC 16 H 100	4	1108	28	64,68	63,31	46	67	31	—	22	9		
JC 17 H 100	4	1210	32	68,72	67,35	46	77	31	—	25	6		
JC 18 H 100	4	1210	32	72,77	71,40	56	80	31	—	25	6		
JC 19 H 100	4	1210	32	76,81	75,44	56	84	31	—	25	6		
JC 20 H 100	4	1210	32	80,85	79,48	56	88	31	—	25	6		
JC 21 H 100	4	1210	32	84,89	83,52	62	94	32	—	25	7		
JC 22 H 100	4	1210	32	88,94	87,57	62	94	32	—	25	7		
JC 23 H 100	4	1610	42	92,98	91,61	71	96	32	—	25	7		
JC 24 H 100	4	1610	42	97,02	95,65	71	104	32	—	25	7		
JC 25 H 100	4	1610	42	101,06	99,69	78	104	32	—	25	7		
JC 26 H 100	4	1610	42	105,11	103,74	78	108	32	—	25	7		
JC 27 H 100	4	1610	42	109,15	107,78	86	113	32	—	25	7		
JC 28 H 100	4	1610	42	113,19	111,92	86	118	32	—	25	7		
JC 29 H 100	4	1610	42	117,23	115,86	95	121	32	—	25	7		
JC 30 H 100	4	1610	42	121,28	119,91	95	129	32	—	25	7		
JC 32 H 100	8	1610	42	129,36	127,99	110	137	32	82	25	7		
JC 33 H 100	8	1610	42	133,40	132,03	112	137	32	82	25	7		
JC 34 H 100	8	1610	42	137,45	136,08	112	142	32	82	25	7		
JC 35 H 100	8	1610	42	141,49	140,12	120	145	32	82	25	7		
JC 36 H 100	8	1610	42	145,53	144,16	120	151	32	82	25	7		
JC 38 H 100	8	1610	42	153,62	152,25	136	158	32	82	25	7		
JC 40 H 100	8	1610	42	161,70	160,33	136	168	32	82	25	7		
JC 44 H 100	7	2012	50	177,87	176,50	162	191	32	110	32	—		
JC 45 H 100	7	2012	50	181,91	180,54	162	189	32	110	32	—		
JC 48 H 100	7	2012	50	194,04	192,67	168	199	32	110	32	—		
JC 49 H 100	12	2012	50	198,08	196,71	172	—	34	110	32	1		
JC 50 H 100	12	2012	50	202,13	200,76	172	—	34	110	32	1		
JC 52 H 100	12	2012	50	210,21	208,84	185	—	34	110	32	1		
JC 60 H 100	12	2012	50	242,55	241,18	217	—	34	110	32	1		
JC 70 H 100	15	2012	50	282,98	281,61	264	—	34	110	32	1		
JC 72 H 100	15	2012	50	291,06	289,69	264	—	34	110	32	1		
JC 82 H 100	15	2012	50	331,49	330,12	312	—	34	110	32	1		
JC 84 H 100	15	2012	50	339,57	338,20	312	—	34	110	32	1		
JC 94 H 100	13	2517	65	380,00	378,63	357	—	34	120	45	5,5		
JC 96 H 100	13	2517	65	388,08	386,71	357	—	34	120	45	5,5		
JC 106 H 100	13	2517	65	428,51	427,14	402	—	34	120	45	5,5		
JC 116 H 100	13	2517	65	468,93	467,56	442	—	34	120	45	5,5		
JC 118 H 100	13	2517	65	477,02	475,65	457	—	34	120	45	5,5		
JC 120 H 100	13	2517	65	485,10	483,73	457	—	34	120	45	5,5		


H150 제이콥 폴리(벨트폭 38^{m/m}용 폴리)

mm

호칭	폴리 타입	부쉬 번호	최대 허용 축경	R ∅	S ∅	U ∅	e ∅	W	H ∅	Y	Z	플랜지	소재
JC 14 H 150	4	1108	28	56,60	55,23	37	62	45	—	22	23	플랜지 타입	cast iron
JC 15 H 150	4	1108	28	60,64	59,27	37	67	45	—	22	23		
JC 16 H 150	4	1108	28	64,68	63,31	46	67	45	—	22	23		
JC 17 H 150	4	1210	32	68,72	67,35	46	77	45	—	25	20		
JC 18 H 150	4	1210	32	72,77	71,40	56	80	45	—	25	20		
JC 19 H 150	4	1210	32	76,81	75,44	56	84	45	—	25	20		
JC 20 H 150	4	1210	32	80,85	79,48	56	88	45	—	25	20		
JC 21 H 150	4	1210	32	84,89	83,52	67	94	45	—	25	20		
JC 22 H 150	4	1210	32	88,94	87,57	67	94	45	—	25	20		
JC 23 H 150	4	1610	42	92,98	91,61	71	98	45	—	25	20		
JC 24 H 150	4	1610	42	97,02	95,65	71	104	45	—	25	20		
JC 25 H 150	4	1610	42	101,06	99,69	78	104	45	—	25	20		
JC 26 H 150	4	1610	42	105,11	103,74	78	108	45	—	25	20		
JC 27 H 150	4	1610	42	109,15	107,78	86	113	45	—	25	20		
JC 28 H 150	4	1610	42	113,19	111,92	86	118	45	—	25	20		
JC 29 H 150	4	1610	42	117,23	115,86	95	121	45	—	25	20		
JC 30 H 150	4	1610	42	121,28	119,91	95	129	45	—	25	20		
JC 32 H 150	8	1610	42	129,36	127,99	110	137	45	82	25	20		
JC 33 H 150	8	1610	42	133,40	132,03	112	137	45	82	25	20		
JC 34 H 150	8	1610	42	137,45	136,08	112	142	45	82	25	20		
JC 35 H 150	8	1610	42	141,49	140,12	120	145	45	82	25	20		
JC 36 H 150	8	1610	42	145,53	144,16	120	151	45	82	25	20		
JC 38 H 150	8	1610	42	153,62	152,25	136	158	45	82	25	20		
JC 40 H 150	8	1610	42	161,70	160,33	136	168	45	82	25	20		
JC 44 H 150	8	2012	50	177,87	176,50	162	191	45	110	32	13		
JC 45 H 150	8	2012	50	181,91	180,54	162	189	45	110	32	13		
JC 48 H 150	8	2012	50	194,04	192,67	168	199	45	110	32	13		
JC 49 H 150	12	2012	50	198,08	196,71	172	—	46	110	32	7		
JC 50 H 150	12	2012	50	202,13	200,76	172	—	46	110	32	7		
JC 52 H 150	12	2012	50	210,21	208,84	185	—	46	110	32	7		
JC 60 H 150	15	2012	50	242,55	241,18	217	—	46	110	32	7		
JC 70 H 150	15	2012	50	282,98	281,61	264	—	46	110	32	7		
JC 72 H 150	15	2012	50	291,06	289,69	264	—	46	110	32	7		
JC 82 H 150	15	2012	50	331,49	330,12	312	—	46	110	32	7		
JC 84 H 150	15	2012	50	339,57	338,20	312	—	46	110	32	7		
JC 94 H 150	15	2517	65	380,00	378,63	357	—	46	120	45	0,5		
JC 96 H 150	15	2517	65	388,08	386,71	357	—	46	120	45	0,5		
JC 106 H 150	15	2517	65	428,51	427,14	402	—	46	120	45	0,5		
JC 116 H 150	15	2517	65	468,93	467,56	442	—	46	120	45	0,5		
JC 118 H 150	15	2517	65	477,02	475,65	457	—	46	120	45	0,5		
JC 120 H 150	15	2517	65	485,10	483,73	457	—	46	120	45	0,5		



4




8


H200 제이콥 폴리(벨트폭 50.48^{m/m}용 폴리)

mm

호칭	폴리 타입	부쉬 번호	최대 허용 축경	R ∅	S ∅	U ∅	e ∅	W	H ∅	Y	Z	플랜지	소재
JC 16 H 200	4	1108	28	64,68	63,31	46	67	58	—	22	36	플랜지 타입	cast iron
JC 17 H 200	4	1210	32	68,72	67,35	52	77	58	—	25	33		
JC 18 H 200	4	1210	32	72,77	71,40	52	80	58	—	25	33		
JC 19 H 200	4	1610	42	76,81	75,44	56	84	58	—	25	33		
JC 20 H 200	4	1610	42	80,85	79,48	56	88	58	—	25	33		
JC 21 H 200	4	1610	42	84,89	83,52	67	94	58	—	25	33		
JC 22 H 200	4	1610	42	88,94	87,57	67	94	58	—	25	33		
JC 23 H 200	4	1610	42	92,98	91,61	71	98	58	—	25	33		
JC 24 H 200	4	1610	42	97,02	95,65	71	104	58	—	25	33		
JC 25 H 200	4	1610	42	101,06	99,69	78	104	58	—	25	33		
JC 26 H 200	4	1610	42	105,11	103,74	78	108	58	—	25	33		
JC 27 H 200	4	1610	42	109,15	107,78	86	113	58	—	25	33		
JC 28 H 200	4	1610	42	113,19	111,92	86	118	58	—	25	33		
JC 29 H 200	4	1610	42	117,23	115,86	95	121	58	—	25	33		
JC 30 H 200	4	1610	42	121,28	119,91	95	129	58	—	25	33		
JC 32 H 200	4	2012	50	129,36	127,99	110	137	58	—	32	26		
JC 33 H 200	4	2012	50	133,40	132,03	112	137	58	—	32	26		
JC 34 H 200	4	2012	50	137,45	136,08	112	142	58	—	32	26		
JC 35 H 200	8	2012	50	141,49	140,12	120	145	58	102	32	26		
JC 36 H 200	8	2012	50	145,53	144,16	120	151	58	102	32	26		
JC 38 H 200	8	2012	50	153,62	152,25	136	158	58	110	32	26		
JC 40 H 200	8	2012	50	161,70	160,33	136	168	58	110	32	26		
JC 44 H 200	8	2012	50	177,87	176,50	162	191	58	110	32	26		
JC 45 H 200	8	2012	50	181,91	180,54	162	189	58	110	32	26		
JC 48 H 200	8	2517	65	194,04	192,67	168	199	58	120	45	13		
JC 49 H 200	12	2517	65	198,08	196,71	172	—	60	120	45	7,5		
JC 50 H 200	12	2517	65	202,13	200,76	172	—	60	120	45	7,5		
JC 52 H 200	12	2517	65	210,21	208,84	185	—	60	120	45	7,5		
JC 60 H 200	15	2517	65	242,55	241,18	217	—	60	120	45	7,5		
JC 70 H 200	15	2517	65	282,98	281,61	264	—	60	120	45	7,5		
JC 72 H 200	15	2517	65	291,06	289,69	264	—	60	120	45	7,5		
JC 82 H 200	15	2517	65	331,49	330,12	312	—	60	120	45	7,5		
JC 84 H 200	15	2517	65	339,57	338,20	312	—	60	120	45	7,5		
JC 94 H 200	15	2517	65	380,00	378,63	357	—	60	120	45	7,5		
JC 96 H 200	15	2517	65	388,08	386,71	357	—	60	120	45	7,5		
JC 106 H 200	15	2517	65	428,51	427,14	402	—	60	120	45	7,5		
JC 116 H 200	15	2517	65	468,93	467,56	442	—	60	120	45	7,5		
JC 118 H 200	15	2517	65	477,02	475,65	457	—	60	120	45	7,5		
JC 120 H 200	15	2517	65	485,10	483,73	457	—	60	120	45	7,5		




12




15

H300 제이콥 폴리(벨트폭 76^{m/m} 용폴리)


호칭	폴리 타입	부쉬 번호	최대 허용 축경	R ∅	S ∅	U ∅	e ∅	W	H ∅	Y	Z	플랜지	소재
JC 19 H 300	3	1215	32	76,81	75,44	56	84	84	—	38	23	플랜지 타입	cast iron
JC 20 H 300	3	1615	42	80,85	79,48	56	88	84	—	38	23		
JC 21 H 300	3	1615	42	84,89	83,52	65	94	84	—	38	23		
JC 22 H 300	3	1615	42	88,94	87,57	65	94	84	—	38	23		
JC 23 H 300	3	1615	42	92,98	91,61	71	98	84	—	38	23		
JC 24 H 300	3	1615	42	97,02	95,65	71	104	84	—	38	23		
JC 25 H 300	3	1615	42	101,06	99,69	79	104	84	—	38	23		
JC 26 H 300	3	1615	42	105,11	103,74	79	108	84	—	38	23		
JC 27 H 300	3	2012	50	109,15	107,78	86	113	84	—	32	26		
JC 28 H 300	3	2012	50	113,19	111,92	86	118	84	—	32	26		
JC 29 H 300	3	2012	50	117,23	115,86	95	121	84	—	32	26		
JC 30 H 300	3	2012	50	121,28	119,91	95	129	84	—	32	26		
JC 32 H 300	3	2517	65	129,36	127,99	110	137	84	—	45	19,5		
JC 33 H 300	3	2517	65	133,40	132,03	112	137	84	—	45	19,5		
JC 34 H 300	3	2517	65	137,45	136,08	112	142	84	—	45	19,5		
JC 35 H 300	3	2517	65	141,49	140,12	120	145	84	—	45	19,5		
JC 36 H 300	3	2517	65	145,53	144,16	120	151	84	—	45	19,5		
JC 38 H 300	5	2517	65	153,62	152,25	136	158	84	120	45	19,5		
JC 40 H 300	5	2517	65	161,70	160,33	136	168	84	120	45	19,5		
JC 44 H 300	5	2517	65	177,87	176,50	162	191	86	120	45	20,5		
JC 45 H 300	5	2517	65	181,91	180,54	162	189	86	120	45	20,5		
JC 48 H 300	5	2517	65	194,04	192,67	168	199	86	120	45	20,5		
JC 49 H 300	12	2517	65	198,08	196,71	172	—	86	120	45	20,5		
JC 50 H 300	12	2517	65	202,13	200,76	172	—	86	120	45	20,5		
JC 52 H 300	12	2517	65	210,21	208,84	185	—	86	120	45	20,5		
JC 60 H 300	15	2517	65	242,55	241,18	223	—	86	120	45	20,5		
JC 70 H 300	15	2517	65	282,98	281,61	264	—	86	120	45	20,5		
JC 72 H 300	15	2517	65	291,06	289,69	264	—	86	120	45	20,5		
JC 82 H 300	15	2517	65	331,49	330,12	312	—	86	120	45	20,5		
JC 84 H 300	15	2517	65	339,57	338,20	312	—	86	120	45	20,5		
JC 94 H 300	15	3030	75	380,00	378,63	357	—	86	146	76	5		
JC 96 H 300	15	3030	75	388,08	386,71	357	—	86	146	76	5		
JC 106 H 300	15	3030	75	428,51	427,14	402	—	86	146	76	5		
JC 116 H 300	15	3030	75	468,93	467,56	442	—	86	146	76	5		
JC 118 H 300	15	3030	75	477,02	475,65	457	—	86	146	76	5		
JC 120 H 300	15	3030	75	485,10	483,73	457	—	86	146	76	5		



3




4




5

XH200 제이콥 폴리(벨트폭 50.8^{m/m} 용폴리)


호칭	폴리 타입	부쉬 번호	최대 허용 축경	R ∅	S ∅	U ∅	e ∅	W	H ∅	Y	Z	플랜지	소재
JC 18 XH 200	4	2517	65	127,34	124,55	95	134	64	—	45	19	플랜지 타입	cast iron
JC 19 XH 200	4	2517	65	134,41	131,62	101	142	64	—	45	19		
JC 20 XH 200	4	2517	65	141,49	138,70	101	150	64	—	45	19		
JC 21 XH 200	4	2517	65	148,56	145,77	115	158	64	—	45	19		
JC 22 XH 200	4	2517	65	155,64	152,85	115	166	64	—	45	19		
JC 24 XH 200	4	2517	65	169,79	167,00	129	177	64	—	45	19		
JC 25 XH 200	4	2517	65	176,86	174,07	143	186	64	—	45	19		
JC 26 XH 200	4	2517	65	183,94	181,15	143	191	64	—	45	19		
JC 27 XH 200	5	2517	65	191,01	188,22	157	200	64	120	45	9,5		
JC 28 XH 200	5	2517	65	198,08	195,29	157	209	64	120	45	9,5		
JC 30 XH 200	5	2517	65	212,23	209,44	180	216	64	120	45	9,5		
JC 32 XH 200	5	2517	65	226,38	223,59	195	232	64	120	45	9,5		
JC 34 XH 200	5	2517	65	240,53	237,74	208	261	64	120	45	9,5		
JC 38 XH 200	5	2517	65	268,83	266,03	234	274	64	120	45	9,5		
JC 40 XH 200	5	3020	75	282,98	280,19	242	288	64	146	51	6,5		
JC 46 XH 200	15	3020	75	325,42	322,63	285	—	64	146	51	6,5		
JC 48 XH 200	15	3020	75	339,57	336,78	299	—	64	146	51	6,5		
JC 58 XH 200	15	3020	75	410,32	407,52	370	—	64	146	51	6,5		
JC 60 XH 200	13	3535	90	424,47	421,68	384	—	64	178	89	12,5		
JC 70 XH 200	13	3535	90	495,21	492,42	455	—	64	178	89	12,5		
JC 72 XH 200	13	3535	90	509,36	506,57	469	—	64	178	89	12,5		
JC 78 XH 200	13	3535	90	551,80	549,01	511	—	64	178	89	12,5		
JC 80 XH 200	13	3535	90	565,95	563,16	525	—	64	178	89	12,5		
JC 82 XH 200	13	3535	90	580,10	577,31	539	—	64	178	89	12,5		
JC 84 XH 200	13	3535	90	594,25	591,46	554	—	64	178	89	12,5		



12




13




15

XH300 제이콥 폴리(벨트폭 76.2^{m/m} 용폴리)


호칭	폴리 타입	부쉬 번호	최대 허용 축경	R ∅	S ∅	U ∅	e ∅	W	H ∅	Y	Z	플랜지	소재
JC 18 XH 300	4	2517	65	127,34	124,55	95	134	90	—	45	45	플랜지 타입	cast iron
JC 19 XH 300	4	2517	65	134,41	131,62	95	142	90	—	45	45		
JC 20 XH 300	4	2517	65	141,49	138,70	101	150	90	—	45	45		
JC 21 XH 300	4	2517	65	148,56	145,77	115	158	90	—	45	45		
JC 22 XH 300	4	2517	65	155,64	152,85	115	166	90	—	45	45		
JC 24 XH 300	4	2517	65	169,79	167,00	129	177	90	—	45	45		
JC 25 XH 300	4	2517	65	176,86	174,07	143	186	90	—	45	45		
JC 26 XH 300	4	2517	65	183,94	181,15	143	191	90	—	45	45		
JC 27 XH 300	8	3020	75	191,01	188,22	157	200	90	146	51	39		
JC 28 XH 300	8	3020	75	198,08	195,29	157	209	90	146	51	39		
JC 30 XH 300	8	3020	75	212,23	209,44	172	216	90	146	51	39	플랜지 없음	cast iron
JC 32 XH 300	8	3020	75	226,38	223,59	186	232	90	146	51	39		
JC 34 XH 300	8	3020	75	240,53	237,74	200	261	90	146	51	39		
JC 38 XH 300	8	3020	75	268,83	266,03	228	274	90	146	51	39		
JC 40 XH 300	5	3020	75	282,98	280,19	245	288	90	146	51	19,5		
JC 46 XH 300	12	3020	75	325,42	322,63	285	—	90	146	51	19,5		
JC 48 XH 300	12	3020	75	339,57	336,78	299	—	90	146	51	19,5		
JC 58 XH 300	12	3535	90	410,32	407,52	370	—	90	178	89	0,5		
JC 60 XH 300	12	3535	90	424,47	421,68	384	—	90	178	89	0,5		
JC 70 XH 300	15	3535	90	495,21	492,42	455	—	90	178	89	0,5		
JC 72 XH 300	15	3535	90	509,36	506,57	469	—	90	178	89	0,5		
JC 78 XH 300	15	3535	90	551,80	549,01	511	—	90	178	89	0,5		
JC 80 XH 300	15	3535	90	565,95	563,16	525	—	90	178	89	0,5		
JC 82 XH 300	15	3535	90	580,10	577,31	539	—	90	178	89	0,5		
JC 84 XH 300	13	4040	100	594,25	591,46	554	—	90	215	102	6		



4




5




8

XH400 제이콥 폴리(벨트폭 101.6^{m/m} 용폴리)

호칭	폴리 타입	부쉬 번호	최대 허용 축경	R ∅	S ∅	U ∅	e ∅	W	H ∅	Y	Z	플랜지	소재
JC 18 XH 400	4	2517	65	127,34	124,55	95	134	119	—	45	74	플랜지 타입	cast iron
JC 19 XH 400	4	2517	65	134,41	131,62	95	142	119	—	45	74		
JC 20 XH 400	4	2517	65	141,49	138,70	101	150	119	—	45	74		
JC 21 XH 400	4	2517	65	148,56	145,77	115	158	119	—	45	74		
JC 22 XH 400	4	2517	65	155,64	152,85	115	166	119	—	45	74		
JC 24 XH 400	4	3020	75	169,79	167,00	129	177	119	—	51	68		
JC 25 XH 400	4	3020	75	176,86	174,07	143	186	119	—	51	68		
JC 26 XH 400	4	3020	75	183,94	181,15	143	191	119	—	51	68		
JC 27 XH 400	4	3020	75	191,01	188,22	157	200	119	—	51	68		
JC 28 XH 400	4	3020	75	198,08	195,29	157	209	119	—	51	68		
JC 30 XH 400	8	3020	75	212,23	209,44	172	216	119	146	51	68	플랜지 없음	cast iron
JC 32 XH 400	8	3020	75	226,38	223,59	186	232	119	146	51	68		
JC 34 XH 400	8	3020	75	240,53	237,74	200	261	119	146	51	68		
JC 38 XH 400	8	3020	75	268,83	266,03	228	274	119	146	51	68		
JC 40 XH 400	5	3535	90	282,98	280,19	242	288	119	178	89	15		
JC 46 XH 400	12	3535	90	325,42	322,63	285	—	119	178	89	15		
JC 48 XH 400	12	3535	90	339,57	336,78	299	—	119	178	89	15		
JC 58 XH 400	15	3535	90	410,32	407,52	370	—	119	178	89	15		
JC 60 XH 400	15	4040	100	424,47	421,68	384	—	119	215	102	8,5		
JC 70 XH 400	15	4040	100	495,21	492,42	455	—	119	215	102	8,5		
JC 72 XH 400	15	4040	100	509,36	506,57	469	—	119	215	102	8,5		
JC 78 XH 400	15	4040	100	551,80	549,01	511	—	119	215	102	8,5		
JC 80 XH 400	15	4040	100	565,95	563,16	525	—	119	90	102	8,5		
JC 82 XH 400	15	4040	100	580,10	577,31	539	—	119	90	102	8,5		
JC 84 XH 400	15	4040	100	594,25	591,46	554	—	119	90	102	8,5		



12




13

주문예

JC 18 XH 400 × 45mm

테퍼-퀵 잇수 타입 제이콥 폴리 타입 벨트폭 4인치 축경









15

제이콥 HTD 폴리

미터식 피치를 갖는 HTD 타이밍 벨트용 폴리로서 피치거리에 따라 8M, 14M이
범용적으로 사용되며, 5M과 20M용도 가능하다. 테퍼 부쉬타입으로 장탈착이
신속하여 공장가동시간을 높여 생산성을 높인다.

8M20 제이콥 폴리(벨트폭 20mm용 폴리)

호칭	잇수	폴리형	R mm	S mm	Øe mm	U mm	W mm	H mm	Z mm	Y mm	테퍼-퀵 부쉬	플랜지	소재
JH 22 - 8 M 20	22	4	56.02	54.65	62	38	28	—	6	22	1008	플랜지 타입	cast iron
JH 24 - 8 M 20	24	4	61.12	59.74	67	42	28	—	6	22	1108		
JH 26 - 8 M 20	26	4	66.21	64.84	73	45	28	—	6	22	1108		
JH 28 - 8 M 20	28	4	71.30	69.93	77	52	28	—	6	22	1108		
JH 30 - 8 M 20	30	4	76.39	75.02	84	56	28	—	6	22	1108		
JH 32 - 8 M 20	32	4	81.49	80.12	88	65	28	—	3	25	1610		
JH 34 - 8 M 20	34	4	86.58	85.21	94	66	28	—	3	25	1610		
JH 36 - 8 M 20	36	4	91.67	90.30	98	68	28	—	3	25	1610		
JH 38 - 8 M 20	38	4	96.77	95.39	104	76	28	—	3	25	1610		
JH 40 - 8 M 20	40	4	101.86	100.49	108	80	28	—	3	25	1610		
JH 44 - 8 M 20	44	1	112.05	110.67	121	—	28	99	4	32	2012		
JH 48 - 8 M 20	48	1	122.23	120.86	129	—	28	105	4	32	2012		
JH 56 - 8 M 20	56	1	142.60	141.23	149	—	28	105	4	32	2012		
JH 64 - 8 M 20	64	6	162.97	161.60	168	140	28	110	4	32	2012		
JH 72 - 8 M 20	72	6	183.35	181.97	191	158	28	110	4	32	2012		
JH 80 - 8 M 20	80	9	203.72	202.35	—	178	28	110	4	32	2012		
JH 90 - 8 M 20	90	12	229.18	227.81	—	204	28	110	4	32	2012		



* 플랜지 없는 폴리형

8M30 제이콥 폴리(벨트폭 30mm용 폴리)

호칭	잇수	폴리형	R mm	S mm	Øe mm	U mm	W mm	H mm	Z mm	Y mm	테퍼-퀵 부쉬	플랜지	소재
JH 22 - 8 M 30	22	4	56.02	54.65	62	38	38	—	16	22	1008	플랜지 타입	cast iron
JH 24 - 8 M 30	24	4	61.12	59.74	67	42	38	—	16	22	1108		
JH 26 - 8 M 30	26	4	66.21	64.84	73	45	38	—	16	22	1108		
JH 28 - 8 M 30	28	4	71.30	69.93	77	52	38	—	16	22	1108		
JH 30 - 8 M 30	30	8	76.39	75.02	84	—	38	—	—	38	1615		
JH 32 - 8 M 30	32	8	81.49	80.12	88	—	38	—	—	38	1615		
JH 34 - 8 M 30	34	8	86.58	85.21	94	—	38	—	—	38	1615		
JH 36 - 8 M 30	36	8	91.67	90.30	98	—	38	—	—	38	1615		
JH 38 - 8 M 30	38	8	96.77	95.39	104	—	38	—	—	38	1615		
JH 40 - 8 M 30	40	8	101.86	100.49	108	—	38	—	—	38	1615		
JH 44 - 8 M 30	44	2	112.05	110.67	121	90	38	—	3	32	2012		
JH 48 - 8 M 30	48	2	122.23	120.86	129	98	38	—	3	32	2012		
JH 56 - 8 M 30	56	2	142.60	141.23	149	118	38	—	3	32	2012		
JH 64 - 8 M 30	64	6	162.97	161.60	168	140	38	115	7	45	2517		
JH 72 - 8 M 30	72	6	183.35	181.97	191	158	38	120	7	45	2517		
JH 80 - 8 M 30	80	9	203.72	202.35	—	178	38	120	7	45	2517		
JH 90 - 8 M 30	90	12	229.18	227.81	—	204	38	120	7	45	2517		
JH 112 - 8 M 30	112	12	285.21	283.83	—	260	38	120	7	45	2517		
JH 144 - 8 M 30	144	12	366.69	365.32	—	341	38	120	7	45	2517		

* 플랜지 없는 폴리형

8M50 제이콥 폴리(벨트폭 50mm용 폴리)


호칭	잇수	폴리형	R mm	S mm	Øe mm	U mm	W mm	H mm	Z mm	Y mm	테퍼-퀵 부쉬	플랜지	소재
JH 28 - 8 M 50	28	2	71.30	69.93	77	52	60	—	19	22	1108	플랜지 타입	cast iron
JH 30 - 8 M 50	30	4	76.39	75.02	84	58	60	—	22	38	1615		
JH 32 - 8 M 50	32	4	81.49	80.12	88	60	60	—	22	38	1615		
JH 34 - 8 M 50	34	4	86.58	85.21	94	66	60	—	22	38	1615		
JH 36 - 8 M 50	36	4	91.67	90.30	98	68	60	—	22	38	1615		
JH 38 - 8 M 50	38	4	96.77	95.39	104	75	60	—	22	38	1615		
JH 40 - 8 M 50	40	2	101.86	100.49	108	80	60	—	14	32	2012		
JH 44 - 8 M 50	44	2	112.05	110.67	121	90	60	—	14	32	2012		
JH 48 - 8 M 50	48	2	122.23	120.86	129	100	60	—	14	32	2012		
JH 56 - 8 M 50	56	2	142.60	141.23	149	120	60	—	7.5	45	2517		
JH 64 - 8 M 50	64	5	162.97	161.60	168	138	60	115	7.5	45	2517		
JH 72 - 8 M 50	72	5	183.35	181.97	191	158	60	120	7.5	45	2517		
JH 80 - 8 M 50	80	7	203.72	202.35	—	178	60	140	4.5	51	3020		
JH 90 - 8 M 50	90	7	229.18	227.81	—	204	60	146	4.5	51	3020		
JH 112 - 8 M 50	112	14	285.21	283.83	—	260	60	146	4.5	51	3020		
JH 144 - 8 M 50	144	14	366.69	365.32	—	341	60	146	4.5	51	3020		
JH 168 - 8 M 50	168	14	427.80	426.42	—	402	60	146	4.5	51	3020		
JH 192 - 8 M 50	192	14	488.92	487.54	—	462	60	146	4.5	51	3020		

* 플랜지 없는 폴리형


8M 85 제이콥 폴리(벨트폭 85mm용 폴리)

호칭	잇수	폴리형	R mm	S mm	Øe mm	U mm	W mm	H mm	Z mm	Y mm	테퍼-궤부쉬	플랜지	소재
JH 34 - 8 M 85	34	2	86.58	85.21	94	66	95	—	28.5	38	1615	플랜지 타입	cast iron
JH 36 - 8 M 85	36	2	91.67	90.30	98	68	95	—	28.5	38	1615		
JH 38 - 8 M 85	38	2	96.77	95.39	104	75	95	—	28.5	38	1615		
JH 40 - 8 M 85	40	2	101.86	100.49	108	80	95	—	31.5	32	2012		
JH 44 - 8 M 85	44	2	112.05	110.67	121	90	95	—	31.5	32	2012		
JH 48 - 8 M 85	48	2	122.23	120.86	129	100	95	—	25	45	2517		
JH 56 - 8 M 85	56	2	142.60	141.23	149	120	95	—	25	45	2517		
JH 64 - 8 M 85	64	2	162.97	161.60	168	138	95	—	25	45	2517		
JH 72 - 8 M 85	72	2	183.35	181.97	191	158	95	—	22	51	3020		
JH 80 - 8 M 85	80	7	203.72	202.35	—	178	95	140	22	51	3020		
JH 90 - 8 M 85	90	7	229.18	227.81	—	204	95	146	22	51	3020		
JH 112 - 8 M 85	112	14	285.21	283.83	—	260	95	146	22	51	3020		
JH 144 - 8 M 85	144	14	366.69	365.32	—	341	95	140	9.5	76	3030		
JH 168 - 8 M 85	168	14	427.80	426.42	—	402	95	140	9.5	76	3030		
JH 192 - 8 M 85	192	14	488.92	487.54	—	462	95	140	9.5	76	3030		


* 플랜지 없는 폴리형




6




7



9



12



14

4M 40 제이콥 폴리(벨트폭 40mm용 폴리)

호칭	잇수	폴리형	R mm	S mm	Øe mm	U mm	W mm	H mm	Z mm	Y mm	테퍼-궤부쉬	플랜지	소재
JH 28 - 14 M 40	28	2	124.78	121.98	134	98	54	—	11	32	2012	플랜지 타입	cast iron
JH 29 - 14 M 40	29	2	129.23	126.44	134	100	54	—	11	32	2012		
JH 30 - 14 M 40	30	2	133.69	130.90	142	100	54	—	11	32	2012		
JH 32 - 14 M 40	32	2	142.60	139.81	150	104	54	—	11	32	2012		
JH 34 - 14 M 40	34	2	151.52	148.72	158	110	54	—	4.5	45	2517		
JH 36 - 14 M 40	36	2	160.43	157.63	166	120	54	—	4.5	45	2517		
JH 38 - 14 M 40	38	2	169.34	166.55	177	130	54	—	4.5	45	2517		
JH 40 - 14 M 40	40	2	178.25	175.46	186	138	54	—	4.5	45	2517		
JH 44 - 14 M 40	44	2	196.08	193.28	209	154	54	—	1.5	51	3020		
JH 48 - 14 M 40	48	2	213.90	211.11	216	172	54	—	1.5	51	3020		
JH 56 - 14 M 40	56	5	249.56	246.76	261	207	54	146	1.5	51	3020		
JH 64 - 14 M 40	64	5	285.21	282.41	288	243	54	146	1.5	51	3020		
JH 72 - 14 M 40	72	7	320.86	318.06	—	279	54	146	1.5	51	3020		
JH 80 - 14 M 40	80	14	356.51	353.71	—	314	54	146	1.5	51	3020		
JH 90 - 14 M 40	90	14	401.07	398.28	—	359	54	146	1.5	51	3020		
JH 112 - 14 M 40	112	14	499.11	496.32	—	457	54	146	1.5	51	3020		
JH 144 - 14 M 40	144	14	641.71	638.92	—	600	54	146	1.5	51	3020		

* 플랜지 없는 폴리형

14M 55 제이콥 폴리(벨트폭 55mm용 폴리)

호칭	잇수	폴리형	R mm	S mm	Øe mm	U mm	W mm	H mm	Z mm	Y mm	테퍼-궤부쉬	플랜지	소재
JH 28 - 14 M 55	28	2	124.78	121.98	134	98	70	—	19	32	2012	플랜지 타입	cast iron
JH 29 - 14 M 55	29	2	129.23	126.44	134	100	70	—	19	32	2012		
JH 30 - 14 M 55	30	2	133.69	130.90	142	100	70	—	12.5	45	2517		
JH 32 - 14 M 55	32	2	142.60	139.81	150	104	70	—	12.5	45	2517		
JH 34 - 14 M 55	34	2	151.52	148.72	158	110	70	—	12.5	45	2517		
JH 36 - 14 M 55	36	2	160.43	157.63	166	120	70	—	12.5	45	2517		
JH 38 - 14 M 55	38	2	169.34	166.55	177	130	70	—	12.5	45	2517		
JH 40 - 14 M 55	40	2	178.25	175.46	186	138	70	—	12.5	45	2517		
JH 44 - 14 M 55	44	2	196.08	193.28	209	154	70	—	9.5	51	3020		
JH 48 - 14 M 55	48	2	213.90	211.11	216	172	70	—	9.5	51	3020		
JH 56 - 14 M 55	56	5	249.56	246.76	261	207	70	146	9.5	51	3020		
JH 64 - 14 M 55	64	5	285.21	282.41	288	243	70	146	9.5	51	3020		
JH 72 - 14 M 55	72	7	320.86	318.06	—	279	70	146	9.5	51	3020		
JH 80 - 14 M 55	80	14	356.51	353.71	—	314	70	146	9.5	51	3020		
JH 90 - 14 M 55	90	14	401.07	398.28	—	359	70	146	9.5	51	3020		
JH 112 - 14 M 55	112	14	499.11	496.32	—	457	70	146	9.5	51	3020		
JH 144 - 14 M 55	144	14	641.71	638.92	—	600	70	146	9.5	51	3020		

* 플랜지 없는 폴리형

